







































MFD BY: HEIL TRAILER INTERNATIONAL CO.

DATE OF MFG 05-15

GVWR 68000

LBS*

GAWR ALL AXLES

20000

LBS

30845

KG*

9072

KG

TIRES Dual 11R24.5 +H

AT

120

PSI COLD

RIMS 24.5 X 8.25

827

KPA COLD

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY
STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE.

VIN 5HTAB4323F7H81114

TEST PRES.

5

PSIG

34

KPA

CAPACITY (GAL) 9200

TYPE SEMI TRAILER

WARRANTED UNDER CURRENT PUBLISHED WARRANTY
*BASED ON UNIFORM WEIGHT DISTRIBUTION

202-2700



HEIL TRAILER INTERNATIONAL, CO.
CTMV. AND CT MFR

VIN 5HTAB4323F7H81114 NO. CT INCL'D 5

CTMV CERT DATE 05-15

CT MFR & CERT DATE 05-15

MAX WEIGHT OF LADING (LBS) 58000

MAX LOADING RATE 1300 GPM@ 5 PSIG MAX

MAX UNLOAD RATE 190 GPM@ -375 PSIG MAX

212-2798



HEIL TRAILER INTERNATIONAL CO.
CTMV AND CT MFR

VIN 5HTAB432317H81114 DOT 406AL
MAWD 3.3 PSIG TEST P 5 PSIG ORIG TEST DATE 05-15
DESIGN TEMPE -30 F TO 180 F
TOTAL NOM CAP (GAL) 2500 MAX LADING DENSITY .91 LB/US GAL
CT NOM CAP FRT TO REAR (GAL) 2500 1500 1200 1000 2500 10
EXP SURF AREA FRT TO REAR (SQ FT) 259 189 113 152 245 0
SHELL MTL 5454-H32 HEAD MTL 5454-O WELD MTL EC56
MFD SHELL THK TOP ENDS .182 TOP CTR .194 SIDE .182 BOTTOM .250
MIN SHELL THK TOP ENDS .173 TOP CTR .185 SIDE .173 BOTTOM .232
MFD HEAD THK .204 MIN HEAD THK .173

212-2625

