

































































AL, CO.

MFD BY: HEIL TRAILER INTERNATIONAL CO.

DATE OF MFG 08-13

GVWR 88000 LBS*
39917 KG*

GAWR ALL AXLES 23000 LBS
10433 KG

INCL'D 6

TIRES Dual 11R24.5 H AT 120 PSI COLD

RIMS 24.5 X 8.25 827 KPA COLD

THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S. FEDERAL MOTOR VEHICLE SAFETY
STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE

00

5 PSIG MAX

VIN 6HTAB4625E7L79294 TEST PRES. 5 PSIG

-1 PSIG MAX

CAPACITY (GAL) 12500 34 KPA

TYPE SEMI TRAILER

212-2798



WARRANTED UNDER CURRENT PUBLISHED WARRANTY
BASED ON UNIFORM WEIGHT DISTRIBUTION



HEIL TRAILER INTERNATIONAL, CO.
CTMV AND CT MFR

IS GAL

1040

84

109

TTOM 250

TTOM 232

HEIL TRAILER

VIN 5HTAB4625E7L79294 NO. CT INCL'D 6

CTMV CERT DATE 08-13

CT MFR & CERT DATE 08-13

MAX WEIGHT OF LADING (LBS) 76000

MAX LOADING RATE 1000 GPM @ 5 PSIG MAX

MAX UNLOAD RATE 400 GPM @ -1 PSIG MAX

212-2798

HEIL

MFD
DATE OF MFD

GVWR 88000
39917

TIRES Dual HR

RIMS 24.5 X 8

THIS VEHICLE COM
STANDARDS

VIN 5HTAB4625E7

CAPACITY (GAL)

TYPE SEMI TRAILER

WARRANTED UNDER CURRENT PUE
BASED ON UNIFORM WEIGHT DIST

HEIL TRAILER INTERNATIONAL CO.
CTMV AND CT MFR

VIN 5HTAB4625E7L79294

DOT 406AL

MAWP 33 PSIG TEST P 5 PSIG ORIG. TEST DATE 8-13

DESIGN TEMP 200 F TO -40 F

TOTAL NOM CAP (GAL) 12500 MAX LOADING DENSITY 7.5 LB/US GAL

CT NOM CAP FRT TO REAR (GAL) 3800 1400 1600 3400 1200 1040

EXP SURF AREA FRT TO REAR (SQ FT) 342 114 129 270 84 109

SHELL MTL 5454-H32 HEAD MTL 5454-0 WELD MTL 5356

MFD SHELL THK TOP ENDS .182 TOP CTR .204 SIDE .184 BOTTOM .250

MIN SHELL THK TOP ENDS .173 TOP CTR .189 SIDE .173 BOTTOM .232

MFD HEAD THK .204 MIN HEAD THK .187

212-2825

HEIL
TRAILER